# AA18 - Improving Whiteness of Alumina Trihydrate through Reduction in Colored Organics in Bayer Liquor

## Sagar Pandit<sup>1</sup> and Ameet Ashok Chaure<sup>2</sup>

1. Assistant General Manager- Bayer Process Development
Hindalco Innovation Centre – Alumina, Hindalco Industries Limited, Belagavi, India

2. Manager- Technical

Utkal Alumina International Limited, Odisha, India

#### Abstract



Conventionally Bayer process is used to produce alumina trihydrate (ATH) from bauxite ore involving caustic digestion at elevated temperature and pressure. During dissolution, a good portion of organics degrade resulting in the formation of different organic compounds, viz: oxalate, organics precipitable by evaporation and other organics.

Organics in Bayer process liquor are generally present in the following proportions: 25% as humics, 9% as hxalate, 21% as huilding block organics (aromatics) and 45% as aliphatics (acetate, formate, etc.).

Humics are the major color causing organics which impart a dull color to the alumina trihydrate. This is especially important for chemical grade manufacturers wherein alumina trihydrate is sold as product for cable applications, solid surface and other applications.

Bauxite source has a major impact on the dissolution of humic substances. For instance, the bauxites processed from the Western and Eastern Ghat regions of India have relatively low conversion of organic in liquor as compared to imported sources of bauxite which have almost double the organic conversion. Also considering the non-availability of high-grade bauxites in India, there is a growing need for using imported sources of bauxite for achieving the desired plant efficiencies and consumption factors. However, this tends to have a negative impact on the liquor quality, especially w.r.t organic carbon content as well as humic substances having a major impact on the alumina trihydrate quality.

Although there are different processes available for the reduction of the color causing impurities from the Bayer liquor, the present studies depict the cost-effective process for improving the color properties of alumina trihydrate.

This paper presents a detailed study, conducted with the use of humic removal aids and its effect on the color properties of the products.

**KeyWords:** Bauxite, Bayer process, brightness, color, humate, hydrate, organics.

#### 1. Introduction

Most of the organic impurities present in the Bayer circuit come from bauxite during digestion. A certain fraction comes from additives such as synthetic flocculants, dewatering aids, antifoaming agents and crystal growth modifiers. These compounds are often added to the system to improve process performance. Most of the organics end up in the process as sodium oxalate or carbonate, which are the major degradation products. Some of the organics leave the system by adsorbing onto the bauxite residue or the alumina trihydrate as it precipitates. A certain portion remains which degrades slowly and accumulates within the circuit until an equilibrium concentration is reached.

These organics have a detrimental effect on the Bayer process in general. Some of the organic species have known to directly interfere with the nucleation, agglomeration and crystal growth rate of alumina trihydrate during precipitation. This reduces the precipitation yields substantially. Certain organics are also responsible for changing the morphology of the solid and increasing soda incorporation, thereby lowering the quality of the end product. In terms of cost, the loss of caustic due to formation of sodium organic compounds such as sodium oxalate or carbonate is significant.

The impact of organics is particularly significant in older plants wherein the organic carbon content is saturated over years and this affects the overall process control in the refinery. Even though metallurgical grade alumina manufacturers can still run with higher organic carbon content in liquor without major impact on product quality, the chemical grade alumina manufacturers face issues w.r.t higher soda content, fineness and lower brightness / whiteness, which are the major customer requirements for high end speciality applications.

Hence there is a need to lower the organic carbon content in the liquor to improve the plant efficiency as well as the product quality. Even though there are several methods for reducing the organic carbon content such as use of liquor burning, sintering of bauxite etc., these are highly cost intensive and hence use of additives has emerged as a viable solution. Various additives such as humate removal aids are being developed for reducing the humate content in liquor which has an adverse impact on the product whiteness and brightness.

This paper discusses about the application of humate removal aids for reducing the organic carbon content in liquor thereby improving the whiteness of hydrate.

### 2. Conceptual Approach

The major organic compounds present in Bayer liquor are classified into three categories, which are based on their molecular weight distributions. The first fraction is referred to as "humic matter" and includes all of the high molecular weight material having molecular weights in excess of 500. The second fraction is referred to as "building block organics". The last fraction represents the low molecular weight degradation products.

Essentially approximately 50 % of the total organic carbon in Bayer liquor is present as low molecular weight organic acids. The other 50 % is evenly distributed between the humic matter (25 %) and the "building block" organics (25 %). Humic matter has a major impact on the liquor quality and thereby on the end product quality especially w.r.t whiteness / brightness. Hence a development work was initiated for understanding the impact of additives such as humate removal aids on the humate reduction in liquor and resulting impact on product quality.

## 3. Development of Humate Removal Aid

The process for development of humate removal aid involved the following steps

- **Literature Survey:** Study on origin of humates, its classification, effect on hydrate color & methods of reduction were evaluated in detail.
- **Data Analysis:** The organic carbon profile in liquor across the refinery was analysed to understand the extent of organic carbon input from the liquor. Also, the data on hydrate whiteness/ brightness was analysed.

From Figure 4 it is clearly observed that the hydrate sample is visually whiter than the pretrial hydrate sample.

Thus, from the above laboratory and plant scale evaluation, it can be concluded that the humate removal aids can be successfully applied to Bayer liquor for reducing the Total Organic Carbon content thereby leading to substantial improvement in brightness / whiteness of hydrate.

#### 4. Discussion

This paper presents the application of humate removal aids to Bayer liquor for reducing the Total Organic Carbon content with a view to improve the brightness / whiteness of alumina trihydrate.

The source and distribution of the organics in Bayer liquor is discussed. Normally the major source is bauxite along with a marginal amount from speciality chemicals used in the alumina refinery. Out of the total organics present in the Bayer liquor, the color causing organics or humates account for  $\sim 25$  %. However, the impact of these organics on the Bayer liquor quality as well as that of the end product is significant. This is especially important for chemical grade alumina manufacturers, where hydrate whiteness / brightness is a major requirement from customers.

Even though there are various methods for reducing the organic content in liquor per say, these methods are tedious and not economically viable. However, in the recent years, use of chemicals such as humate removal aids has gained importance owing to its ease of application.

Various trials were conducted with humate removal aid chemicals received from suppliers and the impact on TOC reduction and hydrate whiteness was noted. The lab trials with HA-1 chemical were successful and yielded good results. There was a reduction in humate content in Bayer liquor by  $\sim 10$ -12 % with an improvement in hydrate whiteness by  $\sim 10$  %.

The findings from the successful laboratory trials were translated into plant scale evaluation of HA-1, which also yielded similar results. In fact, the hydrate produced from the trial was visually whiter than the pretrial hydrate sample.

Thus, from the above laboratory and plant scale evaluation, it can be concluded that the humate removal aids can be successfully applied to Bayer liquor for reducing the Total Organic Carbon content thereby leading to substantial improvement in brightness / whiteness of hydrate.

#### 5. References

- 1. F. Picard, D. Audet, Identification of Hydrate Active Organics (HAO) Present in Spent Bayer Liquors, *Alcan International Limited, ARVIDA*, Quebec, Canada, 2002.
- 2. Helene L. Boily, Characterization of the Organic Components in Bayer Liquor A Review, *Alcan International Limited, ARVIDA*, Quebec, Canada, January 1998.